

Last updated: 02/01/2026 01:24:39

# NAVACLEAN 803 - ALKATUFF PHS 200 LTR

Product group: **034** Product number: **4000017**

Navaclean 803 is a heavy duty water based alkaline cleaner and degreaser, specially formulated for cleaning tanker vessels after vegetable oils, animal oils, fatty acids, fish oils, greasers, waxes, oil, sludge, soot carbon deposits, and general dirt and grime.



## Product information

Navaclean 803 is a heavy duty powerful alkaline cleaner based on potassium hydroxide (KOH), for cleaning of tanker vessels after Vegetable oils, animal oils, fatty acids, fish oils, greasers, waxes, oil, sludge, soot carbon deposits, and general dirt and grime.

### Features

- Degreases multiple surfaces very efficiently, as it is formulated with high concentration of surface active ingredients.
- Has excellent deodorising properties, removing odours of aromatic solvents, fish oil residues and other obnoxious smells
- It has numerous cleaning applications including removal of grease, and general dirt & grime
- Free from hydrocarbon solvents
- Safe to use on epoxy coatings, polyurethane coatings and in stainless steel tanks

### Benefits

- Efficiency enhanced by high quality surface-active agents
- Very effective and economical in use
- Highly concentrated cleaning agent that can be diluted with water for multiple cleaning purposes
- Can be discharged according to IMO MEPC.2/Circ.31. and Marpol Annex V
- Biodegradable

## Specification

### General

Invent Hazard Material (IMO/IU) classification	C-49
--	------

### Physical properties

Appearance	Clear colorless to amber liquid
Density [g/ml]	1.05-1.10
Materials compatibility	Avoid contact with aluminum, tin, zinc or their alloys
Odour	None
pH	13-14

## Documents

[IHM & SDoc](#)

[SDoC and MD for IHM](#)

## Directions for use

### Tank Cleaning recommendation:

NAVACLEAN 803 – ALKATUFF PHS can be applied by brush, spray, direct injection method or recirculation method. The recommended cleaning temperature ranges from ambient – 80°C and depends upon the type of cargo residues.

Direct injection method with tank washing machines: Dosage rate 10-50 litres per 1000 litres wash water. (1–5%)

Recirculation method: Use dosage rate of 20-50 litre per 1000 litre wash water

Spot cleaning: Hand spray 30-100% solution. Leave for approx. 30 minutes before rinsing with water.

We recommend using only fresh water, but if not feasible seawater can be used.

## Related products

Is frequently bought together with

**2009028**  
NAVADAN PUMP & SPRAY KIT

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/tank-cleaning/navaclean-803---alkatuff-phs-200-ltr/>