

Last updated: 02/01/2026 01:51:14

NAVACLEAN 818 - COLD WASH 200 LTR

Product group: **034** Product number: **4000027**

Navaclean 818 Coldwash is a general purpose solvent based tank cleaner and degreaser, suitable for all tank coatings and linings.



Product information

Navaclean 818 Coldwash is a general purpose solvent based cleaner and degreaser, specially formulated with a blend of solvents and emulsifiers to provide a broad spectrum cleaner with maximum solvent penetration and efficient emulsification. It can also be used for spot cleaning of petroleum oil residues, petroleum based chemicals and some natural oils. Navaclean 818 can also be used for the washing of chemical tankers carrying Lube Oil under recirculation.

Features

- Specially formulated with a blend of solvents and emulsifiers to provide a broad spectrum cleaner with maximum solvent penetration and efficient emulsification
- Contains emulsifying agents that enable the residues to be easily removed by fresh or salt water
- Can be used for spot cleaning of petroleum oil residues, petroleum based chemicals and some natural oils

Benefits

- Controlled emulsion breakage, allowing cleaned oil to be easily reclaimed
- Suitable for most tank linings
- Can be applied by hand sprayed
- Approved according to MEPC.2/Circ.31, Annex 10 and Marpol Annex V

Specification

General

Invent Hazard Material (IMO/IU) classification	C-49
--	------

Physical properties

Appearance	Colorless to amber liquid
Density [g/ml]	0.80-0.90
Flash Point [°C]	>62
Materials compatibility	Might cause slight swelling on rubber
Odour	Mild
pH	NA

Documents

[IHM & SDoc](#)

[SDoC and MD for IHM](#)

Directions for use

Undiluted Navaclean 818 is recommended for local cleaning and degreasing and may be applied by brush, hand-spray, immersion soaking or any other conventional means. Depending on the type and the amount of residue to be removed it may be necessary to allow up to 6 hours for the cleaner to react before rinsing with either fresh or salt water. Navaclean 818 may also be used by injection or recirculation at strengths up to 5%, at a temperature of 60-80 °C. For specific cleaning instructions, please contact your local specialist or expert.

Related products

Is frequently bought together with

654723
SEACLEAN PLUS 210 LTR

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/tank-cleaning/navaclean-818---cold-wash-200-ltr/>