

NAVACLEAN 897 - IGS CLEANER 200 LTR

Product group: **020** Product number: **4000082**

Navaclean 897 is a heavy duty water based alkaline cleaner and degreaser, specially designed for removal of inert gas soot (IGS).



Product information

Navaclean 897 is a heavy duty water based alkaline cleaner based on potassium hydroxide and other surface active ingredients, specially formulated for removal of inert gas soot (IGS) in cargo tanks, cleaning tanks after inert gas soot, vegetable oils, animal oils, fatty acids, fish oils, greases, waxes, oil, sludge, soot carbon deposits, and general dirt and grim. It can be applied by different methods: recirculation, direct injection and hand spraying using Navadan pump and spray kit.

Features

- Especially formulated to remove Inert Gas Soot (IGS)
- Removes odors
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds
- Safe to use on epoxy coatings

Benefits

- Degreases multiple surfaces very efficiently, as high concentration of active ingredients
- Highly concentrated and can be diluted with water for multiple cleaning purposes
- Numerous cleaning applications including removal of greases, waxes, vegetable and animal oils, fish oils, carbon deposits, dirt and grime
- Efficiency enhanced by high quality surface-active agents
- Biodegradable
- Approved according to IMO MEPC.1/Circ. 590

Specification

General

Invent Hazard Material (IMO/EL) classification	C-49
---	------

Physical properties

Appearance	clear pale yellow liquid
Density [g/ml]	1.05-1.10
pH	>12

Technical data

Not Compatible	Avoid contact with aluminium, tin, zinc or their alloys
-----------------------	---

Documents

[IHM & SDoc](#)

Directions for use

General cleaning

Navaclean 897 can be used for a variety of cleaning tasks. It can be applied by brush, hand spray by use of Navadan pump and spray kit (2009028) as well as high and low pressure tank washing machines.

Cleaning of IGS (Inert Gas Soot) in Cargo Tanks:

Recirculation method with tank washing machines is recommended using a 6-7% solution in freshwater at 70°C

Spot cleaning: Hand spray 33% to 100% solution. Leave for approx. 30 minutes before rinsing with freshwater. Keep surface wet.

Related products

Is frequently bought together with

2009028
NAVADAN PUMP & SPRAY KIT

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/tank-cleaning/navaclean-897---igs-cleaner-200-ltr/>