

# TANKLEEN ADVANCE 210 LTR

Product group: **652**    Product number: **571489**

Unitor™ Tankleen Advance™ is a microemulsion water based tank cleaner. Main application is for hydrocarbon freeing but it may also be used for other tank cleaning purposes where a strong degreasing effect is required.



## Product information

Unitor™ Tankleen Advance™ is low toxic, biodegradable and safe to use. It contains natural solvents linked with easily biodegradable surfactants.

### Features

- Water-based degreaser
- Does not contain nonylphenol ethoxylates or other estrogenic compounds
- Low-toxic
- Non-flammable
- Splits after cleaning, releasing the oil phase for reclamation

### Benefits

- Micro emulsion based formulation that combines the performance of a water and solvent based product into one low toxic product
- Helps with rapid hydrocarbon freeing of tanks

## Specification

### General

<b>Invent Hazard Material (IMO/EU) classification</b>	C-49
---	------

### Physical properties

<b>Appearance</b>	Water white
<b>Density [g/ml]</b>	1,0
<b>Form</b>	Liquid
<b>pH</b>	7,5

### Technical data

<b>Not Compatible</b>	May soften som rubber and synthetic rubber
-----------------------	--

### Performance data

<b>Pump Speed [cpm]</b>	
-------------------------	--

## Approvals

Unitor™ Tankleen Advance™ has been evaluated by the BLG Working Group on the Evaluation of Safety and Pollution Hazards of Chemicals (ESPH) and found to meet the requirements of paragraph 13.5.2 of the MARPOL Annex II and is consolidated into annex 10 of the MEPC.2/Circular

## Documents

[SDoC and MD for IHM](#)

## Directions for use

**Tank cleaning:**

Hydrocarbon freeing after cleaning with solvent based cleaners like UNITOR™ Seaclean Plus™ . Unitor™ Tankleen Advance™ can be used to clean most of the tank coatings. If in doubt, test the cleaner on a small area of tank coating before full scale cleaning starts.

**Spot Cleaning:** Unitor™ Tankleen Advance™ can be hand sprayed neat or diluted up to 5 parts water and left for about 20 to 30 minutes before washing off with water.

**Recirculation Cleaning:**

Use a solution strength between 0.05 to 0.7% i.e. 0.5 to 7 litres per ton wash water. This solution can be reused until no longer effective. The best result will be achieved when the wash solution is heated to max. 35°C. However, there is no temperature limitation for the rinse water.

## Related products

**Is frequently bought together with**

<b>575613</b>	AQUABREAK PX 25 LTR	<b>571661</b>	METAL BRITE 25 LTR
<b>654715</b>	SEACLEAN PLUS 25 LTR		
<b>654723</b>	SEACLEAN PLUS 210 LTR		
<b>571513</b>	ALKLEEN SAFETY LIQ 25 LTR		

**This page is printed from:**

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/tank-cleaning/tankleen-advance-210-ltr/>