

Last updated: 30/04/2025 05:22:10

UNIPOL 25 LTR

Product group: 033 Product number: 736975

Unitor™ Unipol™ is a pH-neutral, liquid concentrated detergent with excellent cleaning qualities. It is especially suitable for hydrocarbon freeing of tanks and is safe on all tank coatings including zinc silicate.



Product information

Unitor™ Unipol™ contains effective but mild and environmentally safe wetting agents and surfactants that allow rapid penetration to remove fats and oils.

Features

- Non-caustic, pH neutral
- Solvent free
- Non-flammable
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds
- IMO approved and listed in Annex 10 of the MEPC.2/Circular

Benefits

- Non-corrosive to metals
- Suitable for all tank-coatings
- Can be used for gas and hydrocarbon-freeing of tanks
- Can be used for deodorizing
- Complies with all environmental regulations and the EU Detergent Regulation

Specification

General

Invent Hazard Material (IMO/EU) classification	C-49
--	------

Physical properties

Appearance	Light yellow
Density [g/ml]	1,025-1,035
Form	Liquid
pH	8.5-9.5

Performance data

Pump Speed [cpm]	
------------------	--

Approvals

Unitor™ Unipol™ has been evaluated by the BLG Working Group on the Evaluation of Safety and Pollution Hazards of Chemicals (ESPH) and found to meet the requirements of paragraph 13.5.2 of the MARPOL Annex II and is consolidated into annex 10 of the MEPC.2/Circular.

Documents

[SDoC and MD for IHM](#)

Directions for use

Dosing method

The most economical method of using UNITOR™ Unipol™ is by recirculation washing, using tank cleaning machines. Make up a solution of 1 - 5% in preferably fresh water in the tank and recirculate. Whenever possible, the cleaning solution should be heated to 50 - 80°C. Rinse off with hot fresh water. Alternatively, hand spray the tank with a 20 - 50% solution of UNITOR™ Unipol™ and allow to stay for 30 - 60 minutes before a final rinse with hot water. When the tank is cleaned to a "water white standard", remove any free water and ventilate until the tank is dry.

Sampling and testing

For the removal of traces of hydrocarbons to a hydrocarbon free wall wash test specification prior to loading of sensitive cargoes. UNITOR™ Unipol™ may also be used as a general purpose economical tank cleaning detergent.

Related products

Is frequently bought together with

589945
GAMAZYME BTC 12 X 1 LTR

571687
DISCLEAN 25 LTR

777707
MAXI-VAP PLUS 25 LTR

777703
ENGINE WATER TREATMENT25 LTR(9108)

777708
MULTI CLEAN 25 LTR