

DIESELPower CFPP 25 LTR

Product group: **650** Product number: **779112**

Unitor™ DieselPower™ CFPP is an excellent product for cold weather operability with marine distillate fuel. The product help to improve the cold flow properties of a marine distillate fuel and reduce the operational temperatures of Pour Point and Cold Filter Plugging Point. Unitor™ DieselPower™ CFPP help to reduce the size of waxes formed and reduce the risk of wax sedimentation in fuel tanks.

Product image

Product information

This product supersedes product no: **779108**

A distillate fuel contains paraffins. The paraffins are molecules that have a tendency to come together and form larger structures as the temperature drops in the fuel. The paraffins can also be referred to as wax and a fuel with high wax content will have a tendency to cause wax formation at higher temperatures. Once the wax particles has formed they are difficult to dissolve back into the fuel.

Features

- Cold flow improver and pour point depressant
- Delays the onset of paraffin crystallization to improve cold flow properties

Benefits

- Enables you to handle the fuel at lower temperatures
- Adds safety in handling of the fuel by reducing the pour point and the Cold Filter Plugging Point of the fuel
- Keep the wax in suspension preventing wax sedimentation and accumulation

Specification

General

Invent Hazard Material (IMO/EU) classification	C-6
---	-----

Physical properties

Density [kg/dm³]	0,90
Flash Point [°C]	>60
Form	Liquid
Pour Point [°C]	-21

Directions for use

Unitor DieselPower CFPP should be dosed to the fuel tank prior to filling. Recommended dosage is one liter to one thousand liter of fuel (1:1000 or 1000 ppm). In case of poor response dosage can be increased to one liter to five hundred liter of fuel (1:500 or 2000 ppm)

Please note: The dosing temperature should always be at least 5oC above the measured cloud point of the fuel.

Dosage of product	1 ton fuel bunkered	10 ton fuel bunkered	50 ton bunkered	100 ton bunkered
1000 ppm	Dose 1 ltr	Dose 10 ltr	Dose 50 ltr	Dose 100 ltr
2000 ppm	Dose 2 ltr	Dose 20 ltr	Dose 100 ltr	Dose 200 ltr

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/fuel-oil-chemicals/distillate-fuel-treatment/dieselpower-cfpp-25-ltr/>