

Product group: 663 Product number: 507820

A wall mounted cabinet of rugged design. The cabinet contain all the core tests for fuel oil and lubricating oil. The equipment is easy to use for the engine room crew.

Unitor Digital Cell provides a refreshed, but familiar, interface with the addition of smart features to enhance the user experience over previous versions of the product. Unitor Digital Cell can continue to function as an offline instrument for single measurements and is able to be operated without smart features until the user chooses to do so.

Unitor Digital Cell can be configured when connected to most personal computers (PC) - Windows and Mac. Sample points and test locations are labelled as Sample Point IDentification (SPID). This creates structure to measurements and ensures no data is accidentally missed. Results are saved to Unitor Digital Cell and can then be imported into a PC. The SPID approach creates an easily retrievable sample point and test history. Setup can include real-time feedback and alarms for optimal monitoring.



Product information

Viscometer

A new design, microprocessor controlled, easy to use, fast and accurate electronic instrument to determine the viscosity of lube oil at ambient temperature but corrected to 40°C, or heated to the standard temperature of 40°C, and for viscosity measurement of Intermediate Fuels heated to 50°C. Estimation of the combustion performance, Calculated Carbon Aromaticity Index (CCAI). Reports directly in cSt, repeat reading in one minute.

Range:

20 - 810 cSt @ 50°C (ISO Fuel Grades RMA 10 RML 55) 20 - 810 cSt @ 40°C (lube oils SAE 5 through SAE 50)

Density Meter

An easy to use, fast instrument to determine the density of a fuel. 850-1010 kg/m3 @ 15°C. Calculates the CCAI.

Compatibility Test

Compatibility and stability determination. Prediction of a fuel's sludging tendencies.

Water in Oil Test

To determine the water content 0-1%, 0-10% or 1-10000 ppm in lube and fuel oil.

TBN Test

For accurate testing of TBN (Total Base Number) in the range of 0-60.

Comprehensive Training Manual included

Features

- Viscometer
- Density Meter
- Compatibility Test
- Water in Oil Test
- TBN Test
- Insolubles Test

Benefits

- All equipment is contained in a robust, metal case that is fully lockable for safe and secure sample storage.
- Certified by Germanischer Lloyd, providing everything you need to ensure that your fuel samples are compliant with IMO MARPOL 73/78 Annex VI regulations.
- Replacement consumables and a full range of bunker samples are easily available through our network.

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

Related products

Accessories

625756

SALT WATER TEST

625749

INSOLUBLES TEST KIT

773156

UNITOR EASYSHIP REAGENT PACK WATER

632406

TBN REAGENT PACK

Spares

532414

COMBINED REPLACEMENT CELL

632521

HYDROMETER HYD900-1.010

HYD 800-1.010

HYD 850-950

Is frequently bought together with

UWF-102 WIRE FEEDER FOR UWI-500TP

LEATHER APRON F/WELDING

WELDERS GLOVES. 6 PAIRS

TIG GLOVES. 6 PAIRS

400 USH SOCKET 1/2" HOSE

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/test-kits-and-reagents/oil-test-kits/the-fuel-oil-test-cabinet2/2009. The state of the s