



# UNITOR HEATED VISCOSITY METER

Product group: **663**      Product number: **773151**

Small, fast and reliable. Measurements without heating (but corrected to 40°C) or heated to 40°C for lube oil viscosity and to 50°C for fuel oil viscosity.



## Product information

The Heated Oil Viscometer is suitable for measuring both fuel oil viscosity & lube oil viscosity from a wide variety of applications including diesel engines, gas and aviation turbines, gear boxes, hydraulics and fuel oils.

Testing fuel oil viscosity is important for verifying the correct grade of fuel is delivered, for calculating combustion performance, plus adjusting of fuel handling and injection systems. Viscosity of lube oil is the most important property with the correct viscosity providing optimum film strength in system clearances, with minimum friction losses and leakage.

## Features

- 110-240 V AC
- Reports directly in cSt, repeat reading in one minute
- Calculation of Calculated Carbon Aromaticity Index (CCAI)
- Clear and comprehensive user instructions
- Monitors changes in lubricating oil viscosity, preventing costly engine and machinery failures
- Verifies correct fuel grade or blend has been delivered
- Checks that fuel viscosity is acceptable for storage, pumping and purifiers
- Estimates the combustion performance (CCAI) of fuel oil
- Correct density from 50°C. to kg/m<sup>3</sup> @ 15°C in vacuo

## Specification

### General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

## Documents

[773151-Heated-Viscosity-Meter](#)

[Overview-773151-Heated-Viscosity-Meter](#)

### This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/test-kits-and-reagents/oil-test-kits/unitor-heated-viscosity-meter/>