

Product group: 661      Product number: 777060

Test kit for the measurement of oxygen in boiler feed and condensate waters.  
This test is used to monitor the performance of chemical oxygen scavengers and mechanical de-aerators.



Product information

This product supersedes product no: 6006361

Chemet sample tubes work by placing the ampoule into the sample and then gently breaking the end off. The correct amount of sample then gets sucked into the ampoule allowing the test to be performed quickly and accurately.

Test Parameter: Dissolved Oxygen (DO) Measuring Range: 0 - 40 ppb MDL: 1 ppm Method: Indigo Carmine Analysis Time: 2 minutes

Supplied as box of 30 ampoules (Inclusive of: Refill, Comparator, adhesive mounting clamp, permanent mounting clamp, sampling tube, and instructions.)

Replacement consumable:

1. OXYGEN REPLACEMENT AMPOULES M340 (777059)

Features

- Premade reagent vials
- Vacuum sealed ampoules

Benefits

- Portable, easy to use for testing of Boiler Feed and Condensate water

Specification

General

Invent Hazard Material (IMO/IU) classification	C-9
--	-----

Documents

[Dissolved-Oxygen-Test-Method](#)

[SDoC and MD for IHM](#)

Related products

Accessories

777059  
OXYGEN REPLACEMENT AMPOULES M340.

Is frequently bought together with

- 777087  
PH7 BUFFER SOLUTION M0359 (125 ML).
- 777181  
PHOSPHATE.PHOTOMETER M0403 0-80 PPM
- 777179  
CHLORIDE PHOTOMETER M0401 0-32 PPM
- 777088  
PH10 BUFFER SOLUTION M0360 (125 ML)
- 777052  
TOTAL HARDNESS TITRATION PACK M204.

This page is printed from:  
<https://www.wilhelmssen.com/product-catalogue/products/marine-chemicals/test-kits-and-reagents/water-test-kits/oxygen-full-kit-0---40-ppb-o2-m341/>