

Last updated: 14/01/2026 12:38:46

# BOILER COAGULANT 25 LTR

Product group: **655** Product number: **571331**

Effective Sludge Control for Cleaner Boiler Systems



Boiler Coagulant is a liquid sludge conditioner designed to prevent sludge deposits on boiler internal surfaces. By keeping sludge dispersed in small particles, it ensures efficient removal through normal blowdown, preventing tube overheating and maintaining optimal boiler performance. This treatment is primarily used alongside standard chemical treatments and can also address minor oil contamination.

## Product information

### Why Choose Boiler Coagulant?

Choosing Boiler Coagulant means opting for reliable performance that ensures effective sludge control and cleaner boiler systems. Its user-friendly liquid formulation simplifies dosing and application, making maintenance straightforward. The comprehensive protection it offers addresses both sludge and minor oil contamination, enhancing boiler reliability.

Invest in Boiler Coagulant today to maintain clean and efficient boiler systems, ensuring optimal performance and extended operational time with our advanced sludge conditioning solution.

### Features

**Liquid Product:** Easy to feed and apply. **Prevents Deposits:** Stops the formation of adherent deposits and sludges in boilers. **Versatile Use:** Applied in conjunction with standard range of boiler water treatment products. **Oil Contamination Control:** Coagulates small amounts of oil for removal by blowdown.

### Benefits

**Maintains Clean Boilers:** Keeps boilers clean and extends operational time between cleanings. **Efficient Sludge Removal:** Keeps sludge dispersed for effective removal by blowdown. **Prevents Overheating:** Avoids tube overheating due to sludge deposits.

## Specification

### General

<b>Invent Hazard Material (IMO/IU) classification</b>	C-9
---	-----

### Physical properties

<b>Appearance</b>	Pale yellow
<b>Density [g/ml]</b>	1.010 to 1.030
<b>Form</b>	Liquid
<b>pH</b>	8.5 to 11.0

## Documents

[SDoC and MD for IHM](#)

## Directions for use

Dosage is 20 ml of treatment daily per ton of boiler capacity. Daily bottom blowdown is required when using Boiler Coagulant to remove suspended sludge particles.

## Related products

Is frequently bought together with

**680843**  
COOLTREAT AL 25 LTR

**571364**  
VAPTREAT 25LTR

**571356**  
ROCOR NB LIQUID 25 LTR

**735977**  
MAR-71 BIOCID (BOX: 3x5 LTR)

**638676**  
EVAPORATOR DEFOAMER 4X5 LTR

**698720**  
AUTOTREAT - 25 LTR

**698712**  
OXYGEN SCAVENGER PLUS 25 LTR

**777710**  
NALFLEET 2000 25 LTR

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/water-treatment-chemicals/boiler-water-treatment/boiler-coagulant-25-ltr/>