

# BOILER COAGULANT 25 LTR

Product group: **655**      Product number: **571331**

NALFLEET™ Boiler Coagulant™ is a liquid sludge conditioner designed to prevent sludge deposits on boiler internal surfaces.



## Product information

Sludge is kept dispersed in small particles and conditioned to be removed by normal blowdown. In this way tube overheating due to deposits can be avoided. The treatment is primarily used in conjunction with normal chemical treatment chemicals. Boiler Coagulant can also be used where minor oil contamination has been experienced. Small amounts of oil contamination are coagulated for removal by blowdown. However, it must be noted that if oil contamination is continuous and excessive, off-line cleaning will be required. The source of oil contamination must be stopped immediately.

### Features

- Liquid product, easy to feed
- Prevents the formation of adherent deposits and sludges in boilers
- Used in conjunction with Wilhelmsen Ships Service Chemical Service's standard range of boiler water treatments
- Used to coagulate small amounts of oil which have contaminated the boiler water

### Benefits

- Keeps boilers clean and extends boiler operational time between cleaning
- Keeps sludge dispersed for efficient removal by blowdown

## Specification

### General

Invent Hazard Material (IMO/EU) classification	C-9
--	-----

### Physical properties

Appearance	Pale yellow
Density [g/ml]	1.010 to 1.030
Form	Liquid
pH	8.5 to 11.0

## Documents

[SDoC and MD for IHM](#)

## Directions for use

Dosage is 20 ml of treatment daily per ton of boiler capacity. Daily bottom blowdown is required when using Boiler Coagulant to remove suspended sludge particles.

## Related products

Is frequently bought together with

- 680843**  
COOLTREAT AL 25 LTR
- 571364**  
VAPTREAT 25LTR
- 571356**  
ROCOR NB LIQUID 25 LTR
- 735977**  
MAR-71 BIOCID 3X5L NOT IN USA&CAN
- 638676**  
EVAPORATOR DEFOAMER 4X5 LTR
- 698720**  
AUTOTREAT - 25 LTR
- 698712**  
OXYGEN SCAVENGER PLUS 25 LTR
- 777710**  
NALFLEET 2000 25 LTR

