

Product group: 655      Product number: 777701

NALFLEET™ BWT Liquid Plus™ is a blend of phosphate, alkalinity and polymer dispersants designed for the control of scaling and corrosion in the boiler. NALFLEET™ BWT Liquid Plus™ can be used as a phosphate treatment for low hardness feed waters in boilers operating at pressures up to 40 bar.



Product information

This product supersedes product no: 571265

Features

- Minimises scale formulation, corrosion and sludge accumulation
- Simple to Control
- Effective iron dispersant

Benefits

- Maintains sludge in a non-adherent state for removal by blow down
- Simple test to determine level of treatment
- Can be used for boilers of all pressures

Specification

General

|  |     |
|--|-----|
| Invent Hazard Material (IMO/EU) classification | C-9 |
|--|-----|

Physical properties

|                         |   |
|-------------------------|---|
| Appearance              | Pale Yellow   |
| Density [g/ml]          | 1.45 - 1.47   |
| Form                    | Liquid  |
| Materials compatibility | Polypropylene, PVC, Polyethylene, Nylon, Stainless Steel, Viton, Buna –N, Neoprene, Butyl Rubber, Nitrile Rubber, CAF, PTFE |
| pH                      | 14  |

Technical data

|                |  |
|----------------|--|
| Not Compatible | Aluminium, Brass, Copper, Zinc, Light Alloys, Natural Rubber |
|----------------|--|

Documents

[SDoC and MD for IHM](#)

Directions for use

Dosing Method

NALFLEET™ BWT Liquid Plus is best applied neat or diluted with condensate or evaporated water to any convenient strength and applied on a continuous basis using a suitable chemical dosing pump.

Sampling and Testing

Control is by simple boiler water tests for alkalinity.

Dosing and Control

The dosage rate of NALFLEET™ BWT Liquid Plus sufficient to produce a P alkalinity in the boiler water of 100ppm is 0.4 liters/1,000 liters of water. NALFLEET™ BWT Liquid Plus is strongly alkaline. Tanks and feeding equipment should be constructed of suitably resistant material such as polypropylene, PVC, polyethylene, mild steel, cast iron or stainless steel. Avoid the use of brass or light alloys.

Related products

Accessories

739482  
SPECTRAPAK 311

Is frequently bought together with

774828  
CONDENSATE CONTROL 25 LTR

680843  
COOLTREAT AL 25 LTR

571364  
VAPTREAT 25LTR

571356  
ROCOR NB LIQUID 25 LTR

735977  
MAR-71 BIOCIDES 3X5L NOT IN USA&CAN

638676  
EVAPORATOR DEFOAMER 4X5 LTR  
777710  
NALFLEET 2000 25 LTR

**This page is printed from:**  
<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/water-treatment-chemicals/boiler-water-treatment/bwt-liquid-plus-25-ltr/>