

Last updated: 04/07/2025 01:01:19

OXYTREAT 25 LTR

Product group: 655 Product number: 777713

NALFLEET™ Oxytreat™ is a blend of selected tannins for corrosion protection in low to medium pressure steam boilers

Product information

This product supersedes product no: 777241

Features

- Iron/tannate film protects metal surface
- Removes oxygen, protecting boiler and steam lines
- Low toxicity
- Protects feed tank and feed lines

Benefits

- Protects feed tank, feed lines and boiler metal
- Does not add to boiler TDS

Specification

General

Invent Hazard Material (IMO/EU) classification

Physical properties

Appearance	Brown
Density [g/ml]	1.1
Form	Liquid
рН	5.2 to 6.0

Documents

SDoC and MD for IHM

Directions for use

NALFLEETTM Oxytreat is formulated to provide corrosion protection for the feed and boiler system and when used in conjunction with Multi-plus provides a total treatment programme.

C-9

Dosing Method

NALFLEET[™] Oxytreat is best applied by continuous injection to the boiler feed tank using a suitable chemical metering pump to maintain the target reserve in the boiler. NALFLEET[™] Oxytreat is normally dosed at around 15mls per ton of steam to provide 120-160 ppm of tannin in the boiler water,

Sampling and Testing

NALFLEETTM Oxytreat is best applied neat or diluted with condensate or evaporated water to any convenient strength using a suitable chemical dosing pump. The product should be applied to the boiler feed tank or feed line to ensure adequate mixing.

Related products

Accessories Test Kits for Tannin, P Alkalinity, Chloride and Nitrite

777100 BOILER PLUS TEST KIT MO380

Is frequently bought together with 680843 COOLTREAT AL 25 LTR 571356 ROCOR NB LIQUID 25 LTR 735977 MAR-71 BIOCIDE 3X5L NOT IN USA&CAN 638676 EVAPORATOR DEFOAMER 4X5 LTR





This page is printed from

https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/water-treatment-chemicals/boiler-water-treatment/oxytreat-25-ltr/