

Last updated: 01/10/2024 03:21:09

HOUSING 20-1" WITH PRESSURE GAUGE

Product group: **654** Product number: **735116**

NalFleet HOUSING 20-1" WITH PRESSURE GAUGE": is a housing to use together with Corrosion Shield 20-1"/Corrosion Treat 20-1"/Corrosion Block 20-1"



Product information

Features

- Designed for to be used for the following operating conditions, maximum pressure < 8.0 BarG, minimum temperature: 4.0 Deg C maximum temperature: < 45.0 Deg C
- Inlet & outlet connection: 1" BSP thread
- Housing Material: Plastic, non-toxic, suitable for potable water
- O Ring: EPDM
- Pressure Gauge: 0-12 BarG

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[Corrosion Block 20-1 Installation & Maintenance Manual V1 27092024](#)

[735116 \(SDoC And MD For IHM\)](#)

[Corrosion Shield 20-1 Installation & Maintenance Manual V1 270924](#)

Directions for use

A housing to use together with Corrosion Shield 20-1"/Corrosion Treat 20-1"/Corrosion Block 20-1"

Related products

Is consumable by

735101
CORROSION SHIELD 20-1"

735106
CORROSION BLOCK 20-1"

735111
CORROSION TREAT 20-1"

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/water-treatment-chemicals/housing--20-1-with-pressure-gauge/>