

Product group: 659 Product number: 777201

NALFLEET™ RO Surfactant Cleaner™ has been developed for the cleaning of reverse osmosis (RO), nano-filtration (NF) and ultra-filtration (UF) membranes. NALFLEET™ RO Surfactant Cleaner™ is a formulation based on an anionic surfactant and is highly effective in removing colloidal and other organic matter.



Product information

This product supersedes product no: PC-67.11R

Features

- Effective surfactant formulation
- Compatible with wide range of RO membranes
- Liquid formulation

Benefits

- Helps to maintain RO performance
- Effective dosage
- Certified by NSF in accordance with Standard 60 drinking water standards

Specification

General

Invent Hazard Material (IMO/EU) classification	C-49
--	------

Physical properties

Colour	Colorless to pale yellow
Density [g/ml]	1.04
Form	Liquid
Materials compatibility	All membrane elements based on Polyamide chemistries including Thin Film Composite (TFC) membranes when used as prescribed. 304 Stainless Steel Viton O-rings, Buna-N O-rings, Polyethylene piping, Polypropylene piping, HDPE, ULDPE, Epoxy phenolic.
pH	7.0 to 9.0

Technical data

Not Compatible	Coated steel phenolic , Neoprene O-rings, Hypalon O-rings , EPDM O-rings
----------------	--

Note: Viscosity might increase during low temperatures. The recommended storage temperature is between 25-40 C.

Approvals

NSF International Certifies that this product conforms to the requirements of NSF/ANSI Standard 60 - Drinking Water Treatment Chemicals - Health Effects. For off-line use.

[NSF-Listing-23rd-Jan-2012](#)

Documents

[SDoC and MD for IHM](#)

[RO Range Flyer](#)

Directions for use

During normal operation, RO membranes can become fouled, which greatly reduces the efficiency of the system. Deposits build up on the membrane until they cause a reduction in permeate flow and loss in salt rejection. The effects of fouling can lead to poor water quality, loss in production, unscheduled down time and membrane replacement. A regular maintenance and cleaning program can provide return on investment (ROI) results ranging from 100 to 250% by maintaining low pump output pressures and extending the membrane's life.

Elements should be cleaned whenever the normalized permeate flow rate or salt rejection decreases by 10-15% or the differential pressure increases by 10-15% from the original baseline data.

NALFLEET™ RO Surfactant Cleaner conforms to the requirements of NSF/ANSI Standard 60 - Drinking Water Treatment Chemicals - Health Effects.

Dosing and Control

NALFLEET™ RO Surfactant Cleaner should be fed via a closed feed system. A closed feed system is defined as a system in which fluid is moved from a closed storage vessel into a treated media without exposure to the atmosphere except through normal venting or pressure relief devices. NALFLEET™ RO Surfactant Cleaner cleaning solutions are made at 1.0 - 2.0% (by weight) with chlorine-free product water and sodium hydroxide addition to give a pH of 10.5 - 11.0.

Related products

Accessories

737189
CHEM. CLEAN. UNIT W/HEATING, COATED

Consumables

778419
POTABLE WATER TEST KIT
768129
MD100 POOLCONTROL 6IN1

Is frequently bought together with

777852
RO.BISULPHITE 25 LTR LIQUID 38-40%

571356
ROCOR NB LIQUID 25 LTR

777715
RO MLD ACID CLEANER 25 LTR

777718
RO ALKALINE CLEANER 25 LTR

777716
RO SCALE CONTROL 25 LTR

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/water-treatment-chemicals/water-production-treatment/ro-surfactant-cleaner-25-ltr/>