

NOX GUARD AUS40% UREA

Product group: 370 Product number: 912001

NOX GUARD AUS40% UREA reduces Nitrogen Oxide (NOx) emissions in marine engines to help vessels stay compliant with IMO Tier III requirements.



Product information

NOX GUARD AUS40% UREA reduces nitrogen oxide (NOx) emissions in marine diesel engines. Compliant with ISO 18611 standards, this product uses a 40% urea solution to support NOx emissions reduction, assisting your vessels in meeting existing NECA (Nitrogen Oxide Emission Control Areas) regulatory requirements.

Features

- Product available in liquid form and has concentration of 39-41% Urea
- Designed to be used in Selective Catalytic Reduction (SCR) systems
- Reduces NOx emissions in line with IMO Tier III requirements
- Supplied in 1000 LTR IBCs or Tank Trucks depending on terminal restrictions

Benefits

- Trusted quality - ISO 18611 certified for reliability and performance
- NOx emissions management - ensures compliance with IMO Tier III requirements

Specification

Physical properties

Colour	Colourless
Concentration	39 - 41% urea content
Density [kg/m3]	1105 - 1177
Form	Liquid

Approvals

ISO 18611 certified
IMO Tier III compliant

Documents

[NOx Guard AUS40% Flyer](#)

[SDoC and MD for IHM](#)

[NOX Guard Certificate of conformity](#)

[NOX Guard Storage and Handling guidelines](#)

[NOX Guard IHM](#)

Directions for use

Product is ready to use. Can be dosed directly into the SCR.



Our businessPort ServicesShips ServiceShip ManagementNew EnergyOther services
About usAbout WilhelmsenMedia centreContact and
locationsCareersInvestors
Follow usLinkedInInstagram

Privacy notice and cookie policy
Data protection policy
Terms and conditions
Wilhelmsen whistleblowing channel
© 2024 Wilhelmsen. All rights reserved.