

Product group: 422 Product number: 604926

The 2" diaphragm pump is built with the highest quality precision parts. It combines low weight with long lasting, even when used with abrasive fluids, making this pump very cost effective. Chosen by professionals for it's easy, hands-off solution to fluid handling needs.

<u>G</u>

Product information

This is the highest capacity 2-inch double diaphragm pump in its price class. With all the same durable features of the smaller model, the 2150 has 2 in. npt ports that can take on the heavier, more viscous materials and pump them faster with greater tolerance for suspended solids. Model 2150 has an air valve system that is 100% serviceable without disassembly of the wetted parts, saving valuable maintenance time. This pump requires no air line lubrication, which also saves money.

Highest reliability air valves for no stall operation No Lube air valves reduce routine maintenance High flow design with complete range of diaphragm options Rugged construction for long, trouble free performance Ideal for spill response (SOPEP pump) and all types of transfer applications incl. bilges Typical fluids handled by this pump: Oil: Light oil, gear oil, mineral oil Fuel: Diesel, leaded petrol/gasoline, fuel oil Other: Seawater/brine, general waste water, white spirit, alcohol

Features

- Easy maintenance
- Fluid compatiability
- Unique, patented air valves
- Precision-fitted parts

Benefits

- · Quick priming and immediate flow of product
- Handles fluid viscosities up to 5000 cps and solids up to 1/4 in (6,3 mm)
- Excellent for abrasive, low-to-medium viscosity fluids and shear sensitive materials

Specification

General

Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Height [mm]	585
Length [mm]	443
Pumpable solid size [mm]	
Weight [kg]	26.3
Width [mm]	318

Technical data

Air consumption [m³/min]	
Air inlet connection [inch]	1/2
Air pressure [bar]	
Fluid inlet and outlet size [inch]	2
Operating fluid pressure [bar]	
Suction lift [m]	5.48

Performance data

Flow capacity [l/min]	
Pump Speed [cpm]	

Documents

SDoC and MD for IHM

Related products

Accessories

671768

AIR HOSE 1/2", RUBBER, 50 METER COIL

191890

40 UPMPLUG 1/2" MALE BSP.T

607834

AIR VALVE SEAL KIT

607835

FLUID KIT F/MOD 2150 ALUM

607817

SUCTION HOSE 2 IN 5 MTR

729463

HOSE NIPPLES FOR 2150 PUMP

191692

40 USH SOCKET 1/2" HOSE

546036COUPLING KIT ERGO 3000

586784 HEAVY DUTY HOSE 25 MTR

607443

PLASTIC SPATULA

607442 PLASTIC SCOOP-MEDIUM SIZE

607440 PLASTIC BUCKET 10 LTR

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/pumps/double-diaphragm-pumps/double