

Product group: **422** Product number: **604918**

Designed to operate at low air pressure while delivering a smooth, reliable flow. Model 307 pumps are ideal for transferring a wide variety of fluids.

Product information

This pump is designed to operate at low air pressure while delivering a smooth, reliable flow. Model 307 pumps are ideal for transferring a wide variety of fluids. The air motor body is contructed of polypropylene and stainless steel to resist external corrosion. This polypropylene wetted construction model is with Teflon diaphragms and ball checks, suitable for most chemicals including acids and caustic fluids.

Typical applications

Sampling and testing
Drum transfer for fluids up to 1000 centipoise
Circulation of low viscosity inks, detergents and chemicals
Fluid circulation and evacuation
Waste fluid removal
On-demand batch chemical metering
Low viscosity adhesive supply
Consistent low pressure process fluid supply

Typical fluids handled by this pump:

Acids: Hydrochloric Sulphuric, Phosphoric Bleach: Sodium Hypochlorite (<12%)

Base: Sodium Hydroxide, Ammonia, Hydrogen peroxide, Potassium hydroxide

Features

- Easymaintenance
- Fluid compatibility
- Unique, patented air valves
- Precision-fitted parts

Benefits

- · Quick priming and immediate flow of product
- Handles fluid viscosities up to 5000 cps and solids up to 0.09 in (2.29 mm)
- Excellent for abrasive, low-to-medium viscosity fluids and shear sensitive materials

Specification

General

| Invent Hazard Material (IMO/EU) classification | NA |
|--|----|
| | |

Dimensions/Weight

| Height [mm] | 206 |
|--------------------------|-----|
| Length | 203 |
| Pumpable solid size [mm] | |
| Suction height | 3.7 |
| Weight [kg] | 2.2 |
| Width [mm] | 135 |

Technical data

| Air consumption [m³/min] | |
|--------------------------------|--|
| Air inlet connection [inch] | |
| Air pressure [bar] | |
| Ruid inlet connection [inch] | |
| Operating fluid pressure [bar] | |
| Operating temperature [°C] | |
| Suction lift [m] | |

Performance data

| Flow capacity [l/min] | |
|-----------------------|--|
| Pump Speed [cpm] | |

Documents

SDoC and MD for IHM

Related products

Accessories

191874

20 UPMPLUG 1/4" MALE BSP.T

671750

AIR HOSE 3/8"", RUBBER (50 MTR. COIL)

607830

STAINLESS NIPPLE F/307

607833

AIR VALVE KIT

607832

FLUID SECTION REPAIR KIT F/MOD. 307

191684

30 USH SOCKET 3/8" HOSE

Is frequently bought together with

905026 ACETYLENE A-40 FILLING

905034

OXYGEN 0-40 FILLING

752154 REFRIGERATION HANDY TOOLS CASE

REFRIGERANT RECOVERY PACKAGE F/220V

SAFETY SHOVEL

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/pumps/double-diaphragm-pumps/double-d