

Product group: 422      Product number: 666615

The 60:1 features a unique air motor that enables quiet and reliable operation as well easy maintenance.  
The pump is recommended for mobile units and piped installations of moderate length, and are designed to dispense greases up to NLGI 3.



Product information

This product supersedes product no: 655530

The air operated pump has two main parts. One double acting air motor driving and a single acting high pressure pump mechanism. The grease is fed into the pump tube by the piston on the upward stroke and is pushed out through the check valve on the down stroke. The relationship between the areas of the air piston and the pump piston decides the pressure ratio. The pressure ratio is 60:1 and the theoretical static pressure when the pump has stopped is 60 times higher than the air pressure.

The pump is mainly made of an extruded aluminum profile with die-cast aluminum/magnesium alloy top and bottom covers. A stainless steel cover protects the air motor. The 4 meter 3/8" hose has a inner tube of synthetic oil resistant layer. Outer layer is made of durable weather and oil resistant rubber. Reinforced by two braids of compact steel wire.

Features

- Robust carrying handle which connects dire
- The fluid section features a double-acting piston design
- New pump design
- Reduced weight

Benefits

- Easy to carry around and when walking
- Even and steady flow of grease
- 30% increase in performance
- 30% weight reduction

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	
Length [mm]	
Weight [kg]	4.6

Technical data

Air inlet connection [inch]	1/4
Air pressure [bar]	
Fluid outlet connection [inch]	3/8
Ratio	60:1

Documents

[Unitor-Grease-Pump-666615-711309-Instruction-Manual](#)

[SDoC and MD for IHM](#)

Related products

Accessories

- 655548  
GREASE GUN
- 655605  
GREASE HOSE 1/4", 6M
- 655639  
HOSE FLEXIBLE FOR GREASEGUN 45CM
- 655621  
UNION 1/4" MALE X 1/4" MALE

Is frequently bought together with

**510001**  
REGULATOR 510 AC PRESSURE 0-1.5 BAR

**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR

**632786**  
WELDERS GLOVES. 6 PAIRS

**905026**  
ACETYLENE A-40 FILLING

**905034**  
OXYGEN O-40 FILLING

**This page is printed from:**  
<https://www.wilhelmsen.com/product-catalogue/products/pumps/pumps/grease-pumps/portable-greaser-for-20kg-drum/>