

# REFRIGERANT SENSOR IP66

Product group: **607** Product number: **767046**

Refrigerant gas sensor with IP 66 enclosure. Robust sensor for exposed areas



## Product information

This product supersedes product no: **708032**

### Features

- Working temperature range -20° C to +50° C (-4° F to +122° F)
- IP 66 rated
- Improved sensor housing
- Improved sensor with filter to minimise false alarms from background gases
- Improved sensor PCB design with incorporated test points
- Simplified annual maintenance / testing procedures
- Field adjustments to the sensor sensitivity can be carried out very easily. Sensitivity can be set as low as 100 ppm
- Factory supply setting is 500 ppm for low level and 1,000 ppm for high level

### Benefits

- **Crew safety:** safeguards crew members from long-term exposure to high levels of leaked refrigerant gas in enclosed spaces
- **Cost saving:** helps reduce costs due to accidental loss of refrigerants from unmonitored leaks
- **Environmentally sound solution:** reduces the risks of global warming and damaging the ozone layer by instantaneous warning of leaks
- **Class compliant:** the leak detection system is compliant with LRS requirements for their EP notation and the DNV Clean notation

## Specification

### General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

## Documents

[Refrigerant-Leak-Monitor-prodsheet-2014-2](#)

[SDoC and MD for IHM](#)

[Instruction Manual](#)

## Related products

Is frequently bought together with

**233601**

AG 60 252 2.0 X 500MM 0,5KG

**905208**

NITROGEN N-5030 FILLING

**905715**

UNICOOL R-407F 51 KG REFRIGERANT

**752154**

REFRIGERATION HANDY TOOLS CASE

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/refrigeration-equipment/system-equipment--spares/refrigerant-sensor-ip66/>