


Product group: 606      Product number: 711499

A service manifold with high and low pressure gauges and optical sight glass to observe the refrigerant as it flows through the manifold, assisting in assessing the operating performance for a refrigeration systems and assist during recovery or charging processes.  
Also suitable for refrigerants with higher operating pressures like R-410A.



Product information

This product supersedes product no: 597567

Features

- 60 mm glycerine-filled gauges
- Gauge scale for refrigerants like R-410A (higher pressure)
- 2 charging hoses (red & blue) with length of 90 cm; connection 5/16" SAE flare (1/2"-20 UNF) on one end and on the other end 1/4" SAE flare.
- 1 charging hose (yellow) with length of 90cm, 1/4" SAE connection on both ends.
- Hose working pressure of 60 bar
- Valve core depressor connections where applicable

Benefits

- Liquid filled gauges gives accurate reading
- Easy to use with colour-coded valves and hoses

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

- 233601**  
AG 60 252 2.0 X 500MM 0,5KG
- 905208**  
NITROGEN N-5030 FILLING
- 905715**  
UNICOOL R-407F 51 KG REFRIGERANT
- 752154**  
REFRIGERATION HANDY TOOLS CASE

This page is printed from:  
<https://www.wilhelmsen.com/product-catalogue/products/refrigeration-equipment/tools/manifold-set-2-way/>