

Product group: 606 Product number: 587568

The vacuum pump is used for removing moisture and non-condensable gases from refrigeration systems after maintenance or repair.



The pump is supplied with a Vacuum pump oil (0.95 l). The oil is made from a paraffinic mineral oil base, to be used in deep vacuum applications.

Product information

This product supersedes product no: L13470

Features

- Two stage pump for deep vacuum
- Dual voltage (115/230 V) and Frequency Range (50/60Hz)
- Achievable rating as low as 20 microns
- Displacement 113 l/min @ 60Hz
- Unit is factory wired for high voltage (230V). Refer to operating manual to switch to low voltage (115V) if required.

Benefits

- Built in isolating valve isolates the pump from the system with only a 1/4 turn, making it simple to measure rate of rise
- Can be used on systems using CFC, HCFC and HFC in combination with mineral oil, polyester oil, alkyl benzæen oil and PAG oil
- Referred to as "the long term trouble avoider" among refrigeration specialists
- Gas ballast valve to reduce condensation of moisture
- Two stage pump ensures faster and stable vacuum pull

Specification

General

| | |
|--|-----------|
| Invent Hazard Material (IMO/EU) classification | D-1 |
| Product code | UVP-15401 |

Dimensions/Weight

| | |
|-------------------------|---------------|
| Connection [Size/ Type] | 1/4" and 1/2" |
| Weight [kg] | 12 |

Approvals

Package complies with all US EPA and EC regulations
CE - TUV and ARI - UL

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

320424
VACUUM PUMP OIL 1 LITRE
613935
RECOVERY UNIT CONNECTION KIT

Is part of bundle

652522
REFRIGERANT RECOVERY PACKAGE F/220V
652511
REFRIGERANT RECOVERY PACKAGE F/110V

Is frequently bought together with

233601
AG 60 252 2.0 X 500MM 0,5KG
905208
NITROGEN N-5030 FILLING
905715
UNICOOL R-407F 51 KG REFRIGERANT
752154
REFRIGERATION HANDY TOOLS CASE