

Product group: **606** Product number: **597658**

The heavy duty pump is used for removing moisture and non-condensable gases from large refrigeration installations.

The pump is supplied with a Vacuum pump oil (0.95 l). The oil is made from a paraffinic mineral oil base, to be used in deep vacuum applications.

Product information

Features

- Two stage deep vacuum
- Dual voltage (115/230 V) and frequency model (50/60 Hz)
- Achievable rating as low as 20 microns
- Displacement 280 l/min

Benefits

- Built in isolating valve isolates the pump from the system with only a 1/4 turn, making it simple to measure rate of rise
- Can be used on systems using CFC, HCFC and HFC in combination with mineral oil, polyester oil, alkyl benzene oil and PAG oil
- Referred to as "the long term trouble avoider" among refrigeration specialists
- Gas ballast valve to reduce condensation of moisture

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
Product code	LVP-15121A

Dimensions/Weight

Connection [Size/ Type]	1/4" and 1/2"
Weight [kg]	18

Approvals

Package complies with all US EPA and EC regulations
CE - TUV and ARI - UL

Documents

[SDoC and MD for IHM](#)

[Vacuum Pump Instruction Manual](#)

[Sdoc & MD for IHM](#)

Related products

Is accessory to

597674
VACUUM PUMP OIL 5 LITRE
320424
VACUUM PUMP OIL 1 LITRE

Is frequently bought together with

233601
AG 60 252 2.0 X 500MM 0,5KG
905208
NITROGEN N-5030 FILLING
905715
UNICOOL R-407F 51 KG REFRIGERANT
752154
REFRIGERATION HANDY TOOLS CASE

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/refrigeration-equipment/tools/vacuum-pump-110220v/>