

Product group: 324 Product number: 411257

Chafe guard fitting to the main line. Chafe guard will help you to protect the main line in exposed places where chafing occurs. Using the chafe guard will prolong the lifetime of your ropes.



Product information

The distinctive red chafe guards of Timm have been protecting rope assets since 2012. These high tenacity guards are suitable for all rope types (except steel wire). OCIMF states that a rope's ability to "resist external abrasion damage may be improved by the addition of an abrasion resistant overall jacket". It will also "serve to protect from UV exposure".

Features

- Suitable for all rope types, except steel wire
- 100% high tenacity PES
- Customised sizes
- High melting point (260°C)

Benefits

- Easy to install
- Eye-catching
- Rot-proof
- Lightweight, with a smooth surface
- Excellent UV and heat resistance

Specification

General

| | |
|--|----|
| Invent Hazard Material (IMO/EU) classification | NA |
|--|----|

Physical properties

| | |
|-----------------|---------------------------|
| Construction | Solid plain weaved canvas |
| Density [kg/m3] | 1.38 |
| Melting point | 260°C |

Performance data

| | |
|------------------|-----------------|
| Water resistance | 0.3% absorption |
|------------------|-----------------|

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/ropes/high-performance-mooring-rope/acera-lng-package/timm-chafe-guard-w90-3m/>