

KLÜBERBIO LM2-46 200 LTR

Product group: **681** Product number: **210075**

KLÜBERBIO LM2-46 is a fully biodegradable, eco-friendly hydraulic fluid based on synthetic ester oils.



Product information

Klüberbio LM2 oils are fully biodegradable, eco-friendly hydraulic fluids based on synthetic ester oils.

Klüberbio LM2 oils are intended for applications in mobile hydraulic systems, e.g. in the marine and offshore industries as well as for use in the building and water engineering sectors. They are also preferred in stationary hydraulic equipment operating in ecologically sensitive environments, e.g. in hydroelectric power plants and waterway locks

Features

- Fully biodegradable, eco-friendly hydraulic fluids based on synthetic ester oils.
- Complies with the U.S. Environmental Protection Agency's requirements for classification as an Environmentally Acceptable Lubricant (EAL) in terms of biodegradability, toxicity and bioaccumulation standards according to Appendix A of the EPA's Vessel General Permit (VGP).
- Meets or even exceeds the minimum requirements of HEES oils according to ISO 15380

Benefits

- Comply with the requirements for Environmentally Acceptable Lubricants as defined in Appendix A of the EPA 2013 VGP (Vessel General Permit).
- Fully biodegradable, non-toxic products reducing environmental impact in the event of leakage Facilitate start-up of hydraulic systems at very low temperatures due to very good viscosity-temperature behaviour and low pour point; can therefore be used in hydraulic systems with high temperature fluctuations.
- In addition, Klüberbio LM2 oils meet or even exceed the minimum requirements of HEES oils according to ISO 15380.

Specification

General

| | |
|--|-----|
| Invent Hazard Material (IMO/EU) classification | C-3 |
|--|-----|

Dimensions/Weight

| | |
|--------------|---------|
| Packing Size | 200 LTR |
|--------------|---------|

Performance data

| | |
|--|--------------------------|
| Anticorrosive properties on steel, DIN ISO 7120, method A, steel, 24 h/60 °C | no rust corrosion degree |
| Copper corrosion, DIN EN ISO 2160, 3 h/100 °C | 1 - 100 corrosion degree |
| Flash point, DIN EN ISO 2592, Cleveland, open-cup apparatus [°C] | >= 200 °C |
| Foam test, ASTM-D 892, ISO 6247, sequence I/24 °C [ml] | <= 150/0 ml |
| Foam test, ASTM-D 892, ISO 6247, sequence II/ 93.5 °C [ml] | <= 80/0 ml |
| Foam test, ASTM-D 892, ISO 6247, sequence III/24°C [ml] | <= 150/0 ml |
| FZG scuffing test, based on DIN ISO 14635-1, A/8.3/90, scuffing load stage | >= 12 |
| Lower service temperature | -45 °C / -49 °F |
| Pour point, DIN ISO 3016 [°C] | <= -50 °C |
| Upper service temperature | 110 °C / 230 °F |

Documents

[SDoC and MD for IHM](#)

Directions for use

KLÜBERBIO LM2-46 is intended for applications in mobile hydraulic systems, e.g. in the marine and offshore industries as well as for use in the building and water engineering sectors. They are also preferred in stationary hydraulic equipment operating in ecologically sensitive environments, e.g. in hydroelectric power plants and waterway locks

Physical properties

| | |
|---|---|
| Appearance | clear |
| Biodegradability of the base oil, acc. to OECD 301 F, (within 28 days) [%] | >= 60 % |
| Colour | green |
| Density at 20°C [g/cm ³] | approx. 0.918 g/cm ³ (DIN 51757) |
| Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C [mm ² /s] | approx. 7.8 mm ² /s |
| Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C [mm ² /s] | approx. 46 mm ² /s |

Technical data

| | |
|---|-----------|
| Chemical composition, type of oil | ester oil |
| ISO viscosity grade of the base oil, DIN ISO 3448 | 46 |
| Shelf life [months] | 48 |
| Vessel General Permit | fulfilled |
| Viscosity index, DIN ISO 2909 | >= 135 |

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/speciality-lubricants/kluberbio-lm2-46-200-ltr/>