

# ALUMAG-W 235 1,0MM 2,0KG

Product group: **090** Product number: **590083**

Unitor Alumag-W is a magnesium alloyed wire for welding all common wrought and cast aluminium alloys, e.g. AlMg, AlMgMn, AlMgSi and AlMg(Cu) alloys. It is specially suited for welds which must be resistant to seawater and high tension, and also where high ductility is required. Use pure Argon as shielding gas.



## Product information

### Features

- Can be used for wrought and cast aluminium alloys
- Seawater resistant deposit

### Benefits

- Large working area
- Welds will not be corroded

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Dimensions/Weight

Diameter [mm]	1.0
Weight [kg]	2

### Technical data

Polarity	DC +
Voltage [V]	23 mains supply
Wire Speed (m/min)	12

Wire for gas metal arc welding of aluminium and aluminium alloys.

## Related products

### Is consumable by

**301301** UWW-301 TP WIRE WELDER

### Is frequently bought together with

**699538** ALUMIN-351N 3.2X350MM 71 PCS 1.1 KG  
**699264** LH-314N 2.5X350MM 161 PCS 4.0 KG  
**699421** 23/14-322N 2.5X300MM 84 PCS 1.7 KG  
**699405** 18/8-321N 2.5X300MM 89 PCS 1.7 KG

**This page is printed from:**

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/arc-welding-wires/alumag-w-235-10mm-20kg/>