

GPS-W 200 0,8MM WELD. WIRE 5,0KG

Product group: **090** Product number: **590117**

Wire for gas metal arc welding of structural steel.



Product information

Features

- Copper coated
- High silicon content
- Can be used for thin as well as heavier sheets

Benefits

- Rusting prevented during storing
- Fluid molten pool makes welding easy
- Large working range

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	0.8
Weight [kg]	5

Technical data

Polarity	DC +
Voltage [V]	22 mains supply
Wire Speed (m/min)	7.5

GPS-W-200 is a copper coated welding wire for welding of unalloyed and low alloyed structural steel. It can be used for welding sheets in thin as well as larger thicknesses. Stable arc and little spatter. Clean all rust, scale and old paint from the area. Use 80/20% Ar/CO₂ or pure CO₂ shielding gas.

Related products

Is frequently bought together with

632794	TIG GLOVES. 6 PAIRS	602979	18/8MO-221 2.0 X 500 MM 0,5KG
633008	CHIPPING HAMMER ST. 2PCS		
335547	ICUNI-30 239 2.5 X 500 MM 2,0KG		
632786	WELDERS GLOVES. 6 PAIRS		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/arc-welding-wires/gps-w-200-08mm-weld.-wire-50kg/>

