

Product group: **095** Product number: **699405** 

Electrode for welding of stainless steel grades SUS304L and SUS316L.

### **Product information**

This product supersedes product no: 606434

Rutile-basic and LMA electrodes for welding corrosion-resistant austenitic steels containing 16-18% Chromium, 10-14% Nickel and 2-3% Molybdenum, e.g. AlSI:316/316L, TP-316/H, CF-3M/8M/8C, CPF 8M/10 MC.

### Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for welding of stainless steel

### **Benefits**

- Electrodes can be exposed longer in the open
- Can be stored for long time without moisture pick up
- In compliance with maritime rules and regulations

### **Specification**

### General

Invent Hazard Material (IMO/EU) classification	NA

### Technical data

AWS	E316L-17
Polarity	AC,DC+

# 

### Dimensions/Weight

Diameter [mm]	2.5
Weight [kg]	1.7

### Performance data

Amperage [A]	90
--------------	----

### **Documents**

SDoC and MD for IHM

### **Related products**

### Accessories

661778

PICKLING GEL 2L F/STAINLESS STEEL

## Is consumable by

669999

ELECTRODE CABINET COMPACT EMPTY

# Is frequently bought together with

699397

18/8-321N 1.6X300MM213 PCS 1,7 KG

699173

GPO-302N 3.2X350MM 190 PCS 5.4 KG

**699264** LH-314N 2.5X350MM 161 PCS 4.0 KG

**233601** AG 60 252 2.0 X 500MM 0,5KG

----

**699165** GPO-302N 2.5X350MM 295 PCS 5,2KG

### This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/188-321n-2.5x300mm-89-pcs-1.7-kg