

Product group: **095** Product number: **699413** 

Electrode for welding of stainless steel grades SUS304L and SUS316L.

#### **Product information**

This product supersedes product no: 606435

Rutile-basic and LMA electrodes for welding corrosion-resistant austenitic steels containing 16-18% Chromium, 10-14% Nickel and 2-3% Molybdenum, e.g. AlSI:316/316L, TP-316/H, CF-3M/8M/8C, CPF 8M/10 MC.

#### **Features**

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for welding of stainless steel

#### **Benefits**

- Electrodes can be exposed longer in the open
- Can be stored for long time without moisture pick up
- In compliance with maritime rules and regulations

### **Specification**

#### General

Invent Hazard Material (IMO/EU) classification	NA

# Dimensions/Weight

Diameter [mm]	3.2
Weight [kg]	1.7

#### Technical data

AWS	E316L-17
Polarity	AC,DC+

#### Performance data

Amperage [A] 135	
------------------	--

### **Documents**

SDoC and MD for IHM

### **Related products**

### Accessories

661778

PICKLING GEL 2L F/STAINLESS STEEL

## Is consumable by

669999

ELECTRODE CABINET COMPACT EMPTY

# Is frequently bought together with

699272

LH-314N 3.2X450MM96 PCS 5KG

699264

LH-314N 2.5X350MM 161 PCS 4.0 KG

699165

GPO-302N 2.5X350MM 295 PCS 5,2KG

699173

GPO-302N 3.2X350MM 190 PCS 5.4 KG

699405

18/8-321N 2.5X300MM89 PCS 1.7 KG

### This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/188-321n-3.2x300mm-54-pcs-1.7-kg

