

Product group: 095      Product number: 699439

Electrode for welding of stainless steel to mild steel, compound steel and stainless steel overlays.



Product information

This product supersedes product no: 606437

Rutile-basic and LMA electrode for welding corrosion-resistant steels among themselves and to mild steels, for clad CrNiMo steels and for corrosion resistant layers on mild steels. Also for heat resistant steel with 19-21% Chromium and 11-13% nickel.

Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for welding of stainless steel to steel and compound steel

Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
------------------------------------------------	----

Dimensions/Weight

Diameter [mm]	3.2
Weight [kg]	2

Technical data

AWS	E 309MbL-17
Polarity	AC,DC +

Performance data

Amperage [A]	120
--------------	-----

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

661778  
PICKLING GEL 2L F/STAINLESS STEEL

Is frequently bought together with

699405  
18/8-321N 2.5X300MM89 PCS 1.7 KG

699421  
23/14-322N 2.5X300MM84 PCS 1.7 KG

699173  
GPO-302N 3.2X350MM 190 PCS 5.4 KG

233601  
AG 60 252 2.0 X 500MM 0,5KG

699165  
GPO-302N 2.5X350MM 295 PCS 5,2KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/2314-322n-3.2x350mm-50-pcs-2.0-kg/>