

Last updated: 09/12/2023 02:00:56

23/14-322N 4.0X350MM 35 PCS 2.0 KG

Product group: **095** Product number: **699447**

Electrode for welding of stainless steel to mild steel, compound steel and stainless steel overlays.



Product information

This product supersedes product no: **606438**

Rutile-basic and LMA electrode for welding corrosion-resistant steels among themselves and to mild steels, for clad CrNiMo steels and for corrosion resistant layers on mild steels. Also for heat resistant steel with 19-21% Chromium and 11-13% nickel.

Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for welding of stainless steel to steel and compound steel

Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
------------------------------------------------	----

Dimensions/Weight

Diameter [mm]	4
Weight [kg]	2

Technical data

AWS	E 309M _L -17
Polarity	AC,DC+

Performance data

Amperage [A]	180
--------------	-----

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

661778
PICKLING GEL 2L F/STAINLESS STEEL

Is frequently bought together with

777710
NALFLEET 2000 25 LTR

699181
GPO-302N 4.0X350MM 120 PCS 5.2 KG

699512
NIFE-334N 3.2X350MM 68 PCS 2.2 KG

699413
18/8-321N 3.2X300MM 54 PCS 1.7 KG

699173
GPO-302N 3.2X350MM 190 PCS 5.4 KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/2314-322n-4.0x350mm-35-pcs-2.0-kg>