

# GPO-302N 2.5X350MM 295 PCS 5,2KG

Product group: **095**    Product number: **699165**

Electrode for welding of mild steel.



## Product information

This product supersedes product no: **535401**

General purpose organic-rutile coated electrodes for unalloyed steels. Easily weldable in all positions including vertical down. Suitable for bridging large gaps. Excellent for all-purpose repair welding of mild steel.

### Features

- Unitor high density polyethylene packing
- Strikes and restricts easily
- All positions including vertical down
- Superb arc stability
- Bridge large gaps
- Approved by classification societies for mild steels

### Benefits

- Long storage lifespan
- Superb for tack welding
- No need to use additional special electrode
- Easy to use
- Can do the job even if edge preparation is not up to standard
- In compliance with maritime rules and regulations

## Specification

### General

<b>Invent Hazard Material (IMO/EU) classification</b>	NA
---	----

### Dimensions/Weight

<b>Diameter [mm]</b>	2.5
<b>Weight [kg]</b>	5.2

### Technical data

<b>AWS</b>	E 6013
<b>Polarity</b>	AC, DC+/-

### Performance data

<b>Amperage [A]</b>	100
---------------------	-----

General Purpose Organic-rutile coated electrodes for unalloyed steels. Easily weldable in all positions including vertical down. Suitable for bridging large gaps. Excellent for all-purpose repair welding of mild steel.

## Approvals

<http://wssproducts.wilhelmsen.com/cgi/manager.cgi?template=pcat>

## Documents

[SDoC and MD for IHM](#)

## Related products

### Is consumable by

**669999** ELECTRODE CABINET COMPACT EMPTY

### Is frequently bought together with

**699264** LH-314N 2.5X350MM 161 PCS 4.0 KG

**699272** LH-314N 3.2X450MM96 PCS 5KG

**699173** GPO-302N 3.2X350MM 190 PCS 5.4 KG

### This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/gpo-302n-2.5x350mm-295-pcs-52kg/>