

Last updated: 01/09/2023 00:00:39

GPO-302N 3.2X350MM 190 PCS 5.4 KG

Product group: **095** Product number: **599173**

Electrode for welding of mild steel.



Product information

This product supersedes product no: **699173**

General purpose organic-rutile coated electrodes for unalloyed steels. Easily weldable in all positions including vertical down. Suitable for bridging large gaps. Excellent for all-purpose repair welding of mild steel.

Features

- Unitor high density polyethylene packing
- Strikes and re-striking easily
- All positions including vertical down
- Superb arc stability
- Bridge large gaps
- Approved by classification societies for mild steels

Benefits

- Long storage lifespan
- Superb for tack welding
- Easy to use
- Can do the job even if edge preparation is not up to standard
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	3.2
Weight [kg]	5.4

Technical data

AWS	E6013
Polarity	AC, DC +/-

Performance data

Amperage [A]	150
--------------	-----

Approvals

Contact Customer Service for 3rd party approvals certificates

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

699181
GPO-302N 4.0X350MM 120 PCS 5.2 KG

699272
LH-314N 3.2X450MMØ6 PCS 5KG

699165
GPO-302N 2.5X350MM 295 PCS 5,2KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/gpo-302n-3.2x350mm-190-pcs-5.4-kg>