

GPO-302N 4.0X350MM 120 PCS 5.2 KG

Product group: **095** Product number: **699181**

Electrode for welding of mild steel.



Product information

This product supersedes product no: **535393**

General purpose organic-rutile coated electrodes for unalloyed steels. Easily weldable in all positions including vertical down. Suitable for bridging large gaps. Excellent for all-purpose repair welding of mild steel.

Features

- Unitor high density polyethylene packing
- Strikes and restricts easily
- All positions including vertical down
- Superb arc stability
- Bridge large gaps
- Approved by classification societies for mild steels

Benefits

- Long storage lifespan
- Superb for tack welding
- No need to use additional special electrode
- Easy to use
- Can do the job even if edge preparation is not up to standard

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	4
Weight [kg]	5.2

Technical data

AWS	E 6013
Polarity	AC, DC+/-

Performance data

Amperage [A]	200
--------------	-----

General Purpose Organic-rutile coated electrodes for unalloyed steels. Easily weldable in all positions including vertical down. Suitable for bridging large gaps. Excellent for all-purpose repair welding of mild steel.

Approvals

<http://wssproducts.wilhelmsen.com/cgi/manager.cgi?template=pcat>

Documents

[SDoC and MD for IHM](#)

Related products

Is consumable by

669999 ELECTRODE CABINET COMPACT EMPTY

Is frequently bought together with

699272 LH-314N 3.2X450MM96 PCS 5KG

699165 GPO-302N 2.5X350MM 295 PCS 5,2KG

699173 GPO-302N 3.2X350MM 190 PCS 5.4 KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/gpo-302n-4.0x350mm-120-pcs-5.2-kg/>