

Last updated: 31/08/2023 00:00:39

GPO-302N 4.0X350MM 120 PCS 5.2 KG

Product group: 095 Product number: 599181

Electrode for welding of mild steel.



Product information

This product supersedes product no: 699181

General purpose organic-rutile coated electrodes for unalloyed steels. Easily weldable in all positions including vertical down. Suitable for bridging large gaps. Excellent for all-purpose repair welding of mild steel.

Features

- Unitor high density polyethylene packing
- Strikes and re-striking easily
- All positions including vertical down
- Superb arc stability
- Bridge large gaps
- Approved by classification societies for mild steels

Benefits

- Long storage lifespan
- Superb for tack welding
- Easy to use
- Can do the job even if edge preparation is not up to standard

Specification

General

| | |
|--|----|
| Invent Hazard Material (IMO/EU) classification | NA |
|--|----|

Dimensions/Weight

| | |
|---------------|-----|
| Diameter [mm] | 4 |
| Weight [kg] | 5.2 |

Technical data

| | |
|----------|-----------|
| AWS | E6013 |
| Polarity | AC, DC+/- |

Performance data

| | |
|--------------|-----|
| Amperage [A] | 200 |
|--------------|-----|

Approvals

Contact Customer Service for 3rd party approvals certificates

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

699272
LH-314N 3.2X450MM96 PCS 5KG

699165
GPO-302N 2.5X350MM295 PCS 5,2KG

699173
GPO-302N 3.2X350MM 190 PCS 5.4 KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/gpo-302n-4.0x350mm-120-pcs-52.2-kg>