

GPR-300H 3.2X450MM 85 PCS 5.8 KG

Product group: **095** Product number: **699231**

High recovery electrode for welding of mild steel.



Product information

This product supersedes product no: **606444**

High recovery rutile type electrodes for unalloyed steels. Easy to use in the horizontal position with a speed of up to 50 cm/min., and a throat thickness up to 3.5 - 6 mm in one layer. Self-releasing slag. Also suited for steels protected with zinc- or iron-oxide based primers.

Features

- Unitor high density polyethylene packing
- High deposition rate
- Can be rested in the joint during welding
- Approved by classification societies for mild steels

Benefits

- Can be stored for long time without moisture pick up
- Greatly improves on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	3.2
Weight [kg]	5.8

Related products

Is frequently bought together with

633198	GAS IGNITOR TRIPL. 2 PCS	699173	GPO-302N 3.2X350MM 190 PCS 5.4 KG
699272	LH-314N 3.2X450MM96 PCS 5KG		
699165	GPO-302N 2.5X350MM 295 PCS 5,2KG		
699249	GPR-300H 4.0X450MM 51 PCS 5.5 KG		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/gpr-300h-3.2x450mm-85-pcs-5.8-kg/>