

LH-314N 2.5X350MM 161 PCS 4.0 KG

Product group: **095** Product number: **699264**

Electrode for welding of mild steel and ship quality steel.



Product information

This product supersedes product no: **605857**

A reliable basic all-around electrode for unalloyed and low alloyed ship quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties. LMA electrode

Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for higher tensile steels
- Deposit recovery 129%

Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	2.5
Weight [kg]	4

Technical data

AWS	E 7018
Polarity	DC +/-

Performance data

Amperage [A]	105
--------------	-----

A reliable basic all-round electrode for unalloyed and low alloyed ships quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties. LMA electrode

Documents

[SDoC and MD for IHM](#)

Related products

Is consumable by

669999 ELECTRODE CABINET COMPACT EMPTY

Is frequently bought together with

233601 AG 60 252 2.0 X 500MM 0,5KG

699173 GPO-302N 3.2X350MM 190 PCS 5.4 KG

699272 LH-314N 3.2X450MM96 PCS 5KG

699165 GPO-302N 2.5X350MM 295 PCS 5,2KG

699405 18/8-321N 2.5X300MM 89 PCS 1.7 KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lh-314n-2.5x350mm-161-pcs-4.0-kg/>