

LH-314N 3.2X450MM96 PCS 5KG

Product group: **095** Product number: **699272**

Electrode for welding of mild steel and ship quality steel.



Product information

This product supersedes product no: **303057**

A reliable basic all-around electrode for unalloyed and low alloyed ship quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties. LMA electrode

Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for higher tensile steels
- Deposit recovery 124%

Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	3.2
Weight [kg]	5

Technical data

AWS	E 7018
Polarity	DC +/-

Performance data

Amperage [A]	155
--------------	-----

A reliable basic all-round electrode for unalloyed and low alloyed ships quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties. LMA electrode

Documents

[SDoC and MD for IHM](#)

Related products

Is consumable by

669999 ELECTRODE CABINET COMPACT EMPTY

Is frequently bought together with

699264	LH-314N 2.5X350MM 161 PCS 4.0 KG
699280	LH-314N 4.0X450MM 78 PCS 5.6 KG
699165	GPO-302N 2.5X350MM 295 PCS 5,2KG
699173	GPO-302N 3.2X350MM 190 PCS 5.4 KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lh-314n-3.2x450mm96-pcs-5kg/>