

Product group: 095      Product number: 699272

Low hydrogen, high tensile electrode for welding of mild steel and ship quality steel.

Product information

This product supersedes product no: 303057

A reliable basic all-around LMA electrode for unalloyed and low alloyed ship quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties.



Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for higher tensile steels
- Deposit recovery 124%

Benefits

- Optimised formula for shipboard maintenance welding giving high deposition and excellent performance
- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	3.2
Weight [kg]	5

Technical data

AWS	E7018
Polarity	DC +/-

Performance data

Amperage [A]	155
--------------	-----

Approvals

Contact Customer Service for 3rd party approvals certificates

Documents

[SDoC and MD for IHM](#)

Related products

Is consumable by

669999  
ELECTRODE CABINET COMPACT EMPTY

Is frequently bought together with

320320  
UWI-320TP WELDING INVERTER  
699173  
GPO-302N 3.2X350MM 190 PCS 5.4 KG  
699280  
LH-314N 4.0X450MM 78 PCS 5.6 KG  
699264  
LH-314N 2.5X350MM 161 PCS 4.0 KG  
699165  
GPO-302N 2.5X350MM 295 PCS 5,2KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lh-314n-3.2x450mm96-pcs-5kg/>