

Product group: 095 Product number: 699280

Low hydrogen, high tensile electrode for welding of mild steel and ship quality steel.

Product information

This product supersedes product no: **303065**

A reliable basic all-around LMA electrode for unalloyed and low alloyed ship quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties.

Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for higher tensile steels
- Deposit recovery 118%

Benefits

- Optimised formula for shipboard maintenance welding giving high deposition and excellent performance
- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
 In compliance with maritime rules and regulations
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification

Dimensions/Weight

Performance data

Amperage [A]

NA

| Diameter [mm] | 4 |
|---------------|-----|
| Weight [kg] | 5.6 |

Technical data

| AWS | E7018 |
|----------|--------|
| Polarity | DC +/- |

Approvals

Contact Customer Service for 3rd party approvals certificates

Documents

SDoC and MD for IHM

Related products

Is consumable by 669999 ELECTRODE CABINET COMPACT EMPTY

Is frequently bought together with

320320 UWI-320TP WELDING INVERTER 699173 GPO-302N 3.2X350MM 190 PCS 5.4 KG 699264 LH-314N 2.5X350MM 161 PCS 4.0 KG 699272 LH-314N 3.2X450MV96 PCS 5KG 699181 GPO-302N 4.0X350MM 120 PCS 5.2 KG

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lh-314n-4.0x450mm-78-pcs-5.6-kg



210