

Product group: 095      Product number: 699298

High recovery electrode for welding of mild and ship quality steel with good charpy impact value.



Product information

High recovery basic type LMA electrode for unalloyed and low alloyed ship quality steels. Easy to use in the flat position by doing contact welding.

Features

- LMA electrode
- Unitor high density polyethylene packing
- High deposition rate
- Can be rested in the joint during welding
- Approved by classification societies for higher tensile steels

Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- Greatly improve on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	4
Weight [kg]	5.5

Technical data

AWS	E 7028
Polarity	AC, DC+

Performance data

Amperage [A]	240
--------------	-----

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

699173  
GPO-302N 3.2X350MM 190 PCS 5.4 KG

699272  
LH-314N 3.2X450MM 96 PCS 5KG

699165  
GPO-302N 2.5X350MM 295 PCS 5,2KG

905034  
OXYGEN O-40 FILLING

905026  
ACETYLENE A-40 FILLING

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lhh-314h-4.0x450mm-54-pcs-5.5-kg>