Wilhelmsen

Product group: **095** Product number: **699306**

High recovery electrode for welding of mild and ship quality steel with good charpy impact value.



Product information

High recovery basic type LMA electrode for unalloyed and low alloyed ship quality steels. Easy to use in the flat position by doing contact welding.

Features

- LMA electrode
- Unitor high density polyethylene packing
- High deposition rate
- Can be rested in the joint during welding
- Approved by classification societies for higher tensile steels

Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- Greatly improve on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Diameter [mm]	5
Weight [kg]	5.5

Technical data

AWS	E7028
Polarity	AC, DC+

Performance data

Amperage [A]	355

Documents

SDoC and MD for IHM

Related products

Is frequently bought together with

699260
GPR-300H 6.0X450MM 23 PCS 5.3KG

699280
LH-314N 4.0X450MM 78 PCS 5.6 KG

699264
LH-314N 2.5X350MM 161 PCS 4.0 KG

699272
LH-314N 3.2X450MM 96 PCS 5KG

699165
GPO-302N 2.5X350MM 295 PCS 5,2KG

This page is printed from:
https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lhh-314h-5.0x450mm-36-pcs-5.5-kg/