

Product group: 095      Product number: 699306

High recovery electrode for welding of mild and ship quality steel with good charpy impact value.



Product information

High recovery basic type LMA electrode for unalloyed and low alloyed ship quality steels. Easy to use in the flat position by doing contact welding.

Features

- LMA electrode
- Unitor high density polyethylene packing
- High deposition rate
- Can be rested in the joint during welding
- Approved by classification societies for higher tensile steels

Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- Greatly improve on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

Specification

General

|                                                |    |
|------------------------------------------------|----|
| Invent Hazard Material (IMO/EU) classification | NA |
|------------------------------------------------|----|

Dimensions/Weight

|               |     |
|---------------|-----|
| Diameter [mm] | 5   |
| Weight [kg]   | 5.5 |

Technical data

|          |         |
|----------|---------|
| AWS      | E 7028  |
| Polarity | AC, DC+ |

Performance data

|              |     |
|--------------|-----|
| Amperage [A] | 355 |
|--------------|-----|

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

- 699260**  
GPR-300H 6.0X450MM23 PCS 5.3KG
- 699280**  
LH-314N 4.0X450MM78 PCS 5.6 KG
- 699264**  
LH-314N 2.5X350MM161 PCS 4.0 KG
- 699272**  
LH-314N 3.2X450MM96 PCS 5KG
- 699165**  
GPO-302N 2.5X350MM295 PCS 5,2KG