

Last updated: 19/08/2025 01:00:37

UPC-NEO NG PLASMA CUTTER COMPLETE

Product group: **192** Product number: **404200**

The UPC-NEO NG is a new-generation, high performance, portable manual plasma cutting and gouging machine. It offers excellent weight-to-cutting ratio, can cut up to 40mm thickness of steel while weighing only 25kg.



Product information

EU Ecodesign Compliant Welding Machine

Supplied with:

- Torch with 6m cable (connected directly to machine)
- Return clamp with 6m cable and DIX25 connector
- 4m primary cable mounted on the machine
- Initial supply consumables kit consisting of 2 x Electrode, 2 x Tip Cutting, 1 x Cartridge and 1 x Shield Cup
- Air regulator with filter and water separator mounted on machine

Note: Plug for the primary cable must fit the socket types used on board and is therefore not included.

Features

- Performs recommended cut of 20mm at cutting speed of 500mm/min and quality cut of 25mm at cutting speed of 250mm/min
- Equipped with Intelligent Voltage Reading (IVR) function to indicate the end of life for plasma consumables and Part In Place (PIP) function to warn if plasma consumables are not correctly mounted on the torch
- Built-in Total Protection (TP) function to protect machine against phase loss from incoming input power supply
- Self-regulation of input supply enables cutting to occur far from the distribution panel, with extension cable of 50m from a 400V 3ph input
- Torch with safety trigger as per CE standard and "Reset" button to avoid accidental trigger
- IP23 ingress protection with high resistance to dust and moisture

Benefits

- Safe and compliant for maritime and outdoor use
- Superior reliability in tough maritime environment
- Excellent cutting performance and versatile as it can cut a wide range of electrically conductive steels such as mild and stainless steels, castings, aluminium, titanium as well as copper alloys
- Quality cut with lesser distortion and smaller Heat-Affected Zone (HAZ) compared to traditional oxy-fuel cutting process
- Spare part kit available for easy repair and to minimise downtime

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
---	-----

Dimensions/Weight

Dimensions L x W x H [mm]	620 x 225 x 360
Weight [kg]	25

Technical data

Air flow [l/min]	150
Air pressure [bar]	5.0 - 5.5
Duty cycle [%]	35%
Ingress protection	IP23S
Temperature class	H
Voltage [V]	3 phase 380-440V 50/60Hz main supply

Documents

[404200 Instruction Manual](#)

[SDoC and MD for IHM](#)

[404200 Troubleshooting Manual_PW](#)

Related products

Accessories

624585

AIR LINE UNIT FIL/REG/LUB

176024

PORTABLE WELD.TABLE

404204

TORCH SL60 WITH 6M CABLE F/UPC-NEO NG

Spares

404208

TOTAL REPAIR KIT F/UPC-NEO NG

Consumables

310336

TIP DRAG CUTTING FOR UPC-310ML/UPC-85ML, SET OF 5 PCS

310334

ELECTRODE FOR UPC-310M/UPC-85ML, SET OF 5 PCS

310335

START CARTRIDGE FOR UPC-310ML/UPC-85ML

310333

TORCH HEAD FOR UPC-310ML/UPC-85ML

310337

SHIELD CUP BODY FOR UPC-310ML/UPC-85ML

404173

SHIELD CUP BODY MAX LIFE FOR UPC-85ML

404169

SHIELD CUP 80-100A FOR UPC-85ML

404161

SHIELD CUP GOUGING FOR UPC-85ML

404202

CONSUMABLES KIT F/UPC-NEO NG

404201

TIP STAND OFF CUTTING F/UPC-NEO NG, SET OF 5 PCS

404203

TIP GOUGING F/UPC-NEO NG, SET OF 5 PCS

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/arc-weldingcutting-machines/upc-neo-ng-plasma-cutter/>