

Product group: 195      Product number: 632885

Cable connector DIX25 male-female complete for single phase welding machine such as UWI-150 TP.



Product information

This product supersedes product no: 530071

Cable connectors must be insulated in such a way that the danger of handling or short-circuiting through the deck is reduced to a minimum.

This applies both to connected and unconnected parts. There should be no possibility of short-circuiting in connected plugs and sockets attached to cables, even if they should come into occasional contact with salt water. There must be good contact and little resistance at the contact areas and at the welding cable connections to the connectors.

Features

- 230 A at 60 % duty cycle
- For cable size 10–25mm<sup>2</sup>

Benefits

- Accidental falling/tripping due to loose cables along decks, in ladders etc. is avoided
- Accidental short circuiting somewhere along the often excessive lengths of live welding cables lying about is prevented
- The need for replacement of damaged lengths of welding cable is eliminated
- Manhandling of long welding cables, often more time consuming and strenuous than the actual welding job, is avoided
- Permanently installed and correctly dimensioned cables ensure more efficient use of power from welding machine

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

699165  
GPO-302N 2.5X350MM 295 PCS 5,2KG

699173  
GPO-302N 3.2X350MM 190 PCS 5.4 KG

632786  
WELDERS GLOVES, 6 PAIRS

699264  
LH-314N 2.5X350MM 161 PCS 4.0 KG

699272  
LH-314N 3.2X450MM96 PCS 5KG