

Last updated: 30/04/2025 05:20:12

WELDING CABLE & CONNECTOR 35 MM² 20M

Product group: 195 Product number: 175786

Welding cable 35mm² x 20m with safety cable connectors.



Product information

Welding cables used on board, on deck or in an engine room, are exposed to rough weather, oil and mechanical wear. The welding cable supplied by Unitor has wear, flame and oil-resistant insulation on a polychloroprene rubber basis.

It is recognized by its marking at regular intervals with the text "Unitor oil resistant welding cable", size of cable, and the standard for welding cable H01N2-D.

The cable is available in cross section areas 35mm², 50mm², 70mm², and 95mm².

Features

- The cable marked H01N2-D means that it is produced to an international harmonized standard
- The standard length cable extensions are fitted with Unitor safety cable connectors for optimal protection. Connection to the machine panel sockets is done with 2 pcs Dix/Unitor conversions
- When cable extensions with safety connectors are used the electrode holder and ground clamp with safety connectors should be used

Benefits

- Unitor welding cable is oil resistant, flame resistant and wear resistant
- The conductor is built up from 0.2mm diameter copper wires to ensure high flexibility

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
--	----

Dimensions/Weight

Weight [kg]	8.30
-------------	------

Performance data

Amperage [A]	375 Maximum Amperage 35% duty cycle
--------------	-------------------------------------

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

632786
WELDERS GLOVES. 6 PAIRS

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding-arc-welding-equipment/cables-and-connectors/welding-cable-35-mm2-20m/>