

Product group: **195**    Product number: **175836**

Welding cable 35 mm<sup>2</sup>, sold per meter basis



### Product information

Welding cables used on board, on deck or in an engine room, are exposed to rough weather, oil and mechanical wear. The welding cable supplied by Unitor has wear, flame and oil-resistant insulation on a polychloroprene rubber basis. It is recognized by its marking at regular intervals with the text "Unitor oil resistant welding cable", size of cable, and the standard for welding cable H01N2-D. H01N2-D means that the cable is produced to an international harmonized standard.

The conductor is built up from 0.2mm diameter tinned copper strands to ensure flexibility.

The cable is available in cross section areas 35mm<sup>2</sup>, 50mm<sup>2</sup>, 70mm<sup>2</sup>, and 90mm<sup>2</sup>

### Features

- Unitor welding cable is oil resistant, flame resistant and wear resistant. The conductor is built up from 0.2mm diameter copper wires to ensure high flexibility
- The Unitor welding cable complies with the harmonised standard HO1N2D for flexible welding cable

### Specification

General		Dimensions/Weight	
Invent Hazard Material (IMO/EU) classification	NA	Weight [kg]	0.415

### Performance data

Amperage [A]	
--------------	--

### Documents

[SDoC and MD for IHM](#)

### Related products

#### Is frequently bought together with

**632893**  
CABLE CONNECTOR DIX70 MALE-FEMALE

**632786**  
WELDERS GLOVES. 6 PAIRS

**699538**  
ALUMIN-351N 3.2X350MM71 PCS 1.1 KG

**699272**  
LH-314N 3.2X450MMØ6 PCS 5KG

#### This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/cables-and-connectors/welding-cable-35-mm2/>