

Product group: 195      Product number: 175851

Welding cable 70 mm<sup>2</sup>, sold per meter basis



Product information

Welding cables used on board, on deck or in an engine room, are exposed to rough weather, oil and mechanical wear. The welding cable supplied by Unitor has wear, flame and oil-resistant insulation on a polychloroprene rubber basis. It is recognized by its marking at regular intervals with the text "Unitor oil resistant welding cable", size of cable, and the standard for welding cable H01N2-D. H01N2-D means that the cable is produced to an international harmonized standard. The conductor is built up from 0.2mm diameter tinned copper strands to ensure flexibility. The cable is available in cross section areas 35mm<sup>2</sup>, 50mm<sup>2</sup> 70mm<sup>2</sup>, and 95mm<sup>2</sup>.

Features

- Unitor welding cable is oil resistant, flame resistant and wear resistant. The conductor is built up from 0.2mm diameter copper wires to ensure high flexibility
- The Unitor welding cable complies with the harmonised standard HO1N2D for flexible welding cable

Specification

General		Dimensions/Weight	
Invent Hazard Material (IMO/IU) classification	NA	Weight [kg]	0.785

Performance data

Amperage [A]	
--------------	--

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

500500  
UWI-500TP WELDING INVERTER  
500102  
UWF-102 WIRE FEEDER FOR UWI-500TP

Is frequently bought together with

632893  
CABLE CONNECTOR DIX70 MALE-FEMALE  
709485  
FLIPVISION WELDING FACE SHIELD  
619098  
FACE SHIELD W/HANDLE

This page is printed from:  
<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/cables-and-connectors/welding-cable-70-mm2/>