

Product group: **195** Product number: **175851**

Welding cable 70 mm<sup>2</sup>, sold per meter basis



## Product information

Welding cables used on board, on deck or in an engine room, are exposed to rough weather, oil and mechanical wear. The welding cable supplied by Unitor has wear, flame and oil-resistant insulation on a polychloroprene rubber basis. It is recognized by its marking at regular intervals with the text "Unitor oil resistant welding cable", size of cable, and the standard for welding cable H01N2-D. H01N2-D means that the cable is produced to an international harmonized standard. The conductor is built up from 0.2mm diameter tinned copper strands to ensure flexibility. The cable is available in cross section areas 35mm<sup>2</sup>, 50mm<sup>2</sup>, 70mm<sup>2</sup>, and 95mm<sup>2</sup>.

### Features

- Unitor welding cable is oil resistant, flame resistant and wear resistant. The conductor is built up from 0.2mm diameter copper wires to ensure high flexibility
- The Unitor welding cable complies with the harmonised standard HO1N2D for flexible welding cable

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Dimensions/Weight

Weight [kg]	0.785
-------------	-------

### Performance data

Amperage [A]	600 Maximum Amperage 35% duty cycle
--------------	-------------------------------------

## Documents

[SDoC and MD for IHM](#)

## Related products

### Is accessory to

**500500**  
UWI-500TP WELDING INVERTER  
**500102**  
UWF-102 WIRE FEEDER FOR UWI-500TP

### Is frequently bought together with

**632893**  
CABLE CONNECTOR DIX70 MALE-FEMALE  
**709485**  
FLIPVISION WELDING FACE SHIELD  
**619098**  
FACE SHIELD W/HANDLE

### This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/cables-and-connectors/welding-cable-70-mm2/>