

Last updated: 30/03/2023 21:02:41

WELDING CABLE 95 MM² 50M W/OUT CONNECTORS

Product group: **195** Product number: **709017**

Welding cable 95 mm² x 50 meter coil.



Product information

Welding cables used on board, on deck or in an engine room, are exposed to rough weather, oil and mechanical wear. The welding cable supplied by Unitor has wear, flame and oil-resistant insulation on a polychloroprene rubber basis.

It is recognized by its marking at regular intervals with the text "Unitor oil resistant welding cable", size of cable, and the standard for welding cable H01N2-D.

The cable is available in cross section areas 35mm², 50mm² 70mm², and 95mm².

Features

- The cable marked H01N2-D means that it is produced to an international harmonized standard

Benefits

- Unitor welding cable is oil resistant, flame resistant and wear resistant
- The conductor is built up from 0.2mm diameter copper wires to ensure high flexibility

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Weight [kg]	53
-------------	----

Performance data

Amperage [A]	730 Maximum Amperage 35% duty cycle
--------------	-------------------------------------

Variants

Product name	Product number	Weight [kg]	Amperage [A]
<u>CABLE DRUM W/CRANK</u>	175729	10.5	
<u>WELDING CABLE & CONNECTOR 35 MM² 10M</u>	175794	4.15	375
<u>WELDING CABLE & CONNECTOR 35 MM² 20M</u>	175786	8.30	375
<u>WELDING CABLE & CONNECTOR 35 MM² 50M</u>	175778	20.75	375
<u>WELDING CABLE & CONNECTOR 50 MM² 10M</u>	175828	5.7	480
<u>WELDING CABLE & CONNECTOR 50 MM² 20M</u>	175810	11.4	480
<u>WELDING CABLE & CONNECTOR 50 MM² 50M</u>	175802	28.5	480
<u>WELDING CABLE & CONNECTOR 70 MM² 50M</u>	183665	39.25	600
<u>WELDING CABLE 95 MM² 50M W/OUT CONNECTORS</u>	709017	53	730

Documents

[SDoc and MD for IHM](#)

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/cables-and-connectors/welding-cable-95-mm2-50m-wout-connectors/?epieditmode=true&>